



TEXRECO CONTRACT EXTRA CLEAR

WALL COVERING

Technical Data Sheet

Revised: 01/10/2018

DESCRIPTION

Ready-mix TRANSPARENT adhesive especially developed for dark and paintable fiber glass contract wall coverings.

- + High strength
- + Does not stain also with dark wall coverings
- + High yield
- + Low V.O.C. content
- + Contains antibacterial and anti-mold additives

Suitable for:

- All kinds of residential and contract wall coverings. with non-woven or fabric backing.
- Fiberglass wall coverings
- Dark or flock wallpaper

SURFACE PREPARATION

All surfaces must be dry, absorbent, strong, free of dust or paints or oils. Any cracks or holes in the wall must be covered with our extra-light GLASTER and in case of imperfections shaved with a normal stucco plaster.

We always recommend the use of our PRIMER AC fixative for consolidation and cleaning.

We recommend using our PRIMER SP (specific for wet walls with fungi and mold) in case of rising damp or too humid.

PREPARATION OF ADHESIVE

TEXRECO CONTRACT EXTRA CLEAR is ready to use. If necessary, dilute with 5% clean water.

APPLICATION

TEXRECO CONTRACT EXTRA CLEAR is applied in a single coat with a brush, roller, spatula or pasting machine.

BRUSH - Apply TEXRECO CONTRACT EXTRA CLEAR on the back of the wall covering. Fold the sheet back on itself and wait 10 - 20 minutes depending from the ambient temperature. Then proceed to apply of the sheet.

Video tutorial: <https://www.youtube.com/watch?v=j7zO9ekpbRg>

ROLLER - Apply TEXRECO CONTRACT EXTRA CLEAR directly on the wall with short wool roll for about 10/15 m². Proceed accordingly to apply the wall covering.

Video tutorial: <https://www.youtube.com/watch?v=2p-pteh2B1>

SPATULA - Apply undiluted TEXRECO CONTRACT EXTRA CLEAR with a toothed spatula no. 1 directly on the wall. For 15 m² proceed to apply the wall coverings.

Video tutorial: <https://www.youtube.com/watch?v=316ytuK36rA>

MACHINE - Dilute TEXRECO CONTRACT EXTRA CLEAR with 5/10% of water before to use the product.

CONSUMPTION

150 - 250 g/m²

CLEANING

We recommend cleaning the wall coverings from excess adhesive and joints with a wet sponge. Possible spillages of the adhesive should be removed immediately.

We also recommend consulting the cleaning instructions of the wall covering's manufacturer before installation.

THE PRODUCT DOES NOT STAIN.

CONTRAINDICATIONS

TEXRECO CONTRACT EXTRA CLEAR is not suitable on non-absorbent surfaces, imperfect prepared substrates and on humid walls.

PACKAGES

| | |
|--------------|-----------------|
| Bucket 5 Kg | code 10004-C-EC |
| Bucket 10 Kg | code 10005-C-EC |
| Bucket 15 Kg | code 10006-C-EC |

STORAGE

TEXRECO CONTRACT EXTRA CLEAR is guaranteed for 24 months from the date of production. Preserve from frost. (+ 5 °C + 40 °C)

TECHNICAL DATA

| | |
|--------------------------|------------------------|
| base: | starch |
| physical appearance: | semi-transparent paste |
| pH: | 6.5 |
| viscosity: | 50,000 to 60,000 cps |
| V.O.C. content: | <0.55 g / l |
| solid content %: | about 35% |
| customs code: | 3506 9190 |
| application temperature: | + 5 °C + 40 °C |
| waiting time: | 0 - 10 minutes |
| open time: | 20 - 30 minutes |
| definitive adhesion: | 48 hours |
| non flammable | |

FINAL PROVISIONS

Keep out of the reach of children and pets. Discharge the waste in special containers for building materials.



A.C.M. Sas di Danese R. & C. | Via XXV Aprile, 62 | 20010 Bareggio /MI
PHONE +39 02 903 611 48 | laboratorio@acm-italy.com | www.acm-italy.com