



# TEXRECO CONTRACT SUPER STRONG

## WALL COVERING

Technical Data Sheet

Revised: 01/10/2018

### DESCRIPTION

Ready-mix adhesive especially developed for all kinds of contract wall coating.

- + Very strength
- + Does not stain
- + High yield
- + Low V.O.C. content
- + Contains antibacterial and anti-mold additives

Suitable for:

- Vinyl contract wall coverings with fabric or non woven backing with a weight up to 1 kg/m<sup>2</sup>
- Fiberglass wall coverings
- Paintables wall coverings

### SURFACE PREPARATION

All surfaces must be dry, absorbent, strong, free of dust or paints or oils.

Any cracks or holes in the wall must be covered with our extra-light GLASTER and in case of imperfections shaved with a normal stucco plaster.

We always recommend the use of our PRIMER AC fixative for consolidation and cleaning.

We recommend using our PRIMER SP (specific for wet walls with fungi and mold) in case of rising damp or too humid.

### PREPARATION OF ADHESIVE

TEXRECO CONTRACT SUPER STRONG is ready to use.  
If necessary, dilute with 5% clean water.

### APPLICATION

TEXRECO CONTRACT SUPER STRONG is applied in a single coat with a brush, roller, spatula or pasting machine.

**BRUSH** - Apply TEXRECO CONTRACT SUPER STRONG on the back of the wall covering. Fold the sheet back on itself and wait 10 - 20 minutes depending from the ambient temperature. Then proceed to apply of the sheet.

Video tutorial: <https://www.youtube.com/watch?v=j7zO9ekpbRg>

**ROLLER** - APPLY TEXRECO CONTRACT SUPER STRONG directly on the wall with short wool roll for about 10/15 m<sup>2</sup>. Proceed accordingly to apply the wall covering.

Video tutorial: <https://www.youtube.com/watch?v=2p-pteh2B1>

**SPATULA** - Apply undiluted TEXRECO CONTRACT SUPER STRONG with a toothed spatula no. 1 directly on the wall. For 15 m<sup>2</sup> proceed to apply the wall coverings.

Video tutorial: <https://www.youtube.com/watch?v=316ytuK36rA>

**MACHINE** - Dilute TEXRECO CONTRACT SUPER STRONG with 5/10% of water before to use the product.

### CONSUMPTION

150 - 250 g/m<sup>2</sup>

### CLEANING

We recommend cleaning the wall coverings from excess adhesive and the joints with a wet sponge.

Possible spillages of the adhesive should be removed immediately. We also recommend consulting the cleaning instructions of the wall covering's manufacturer before installation.

THE PRODUCT DOES NOT STAIN.

### CONTRAINDICATIONS

TEXRECO CONTRACT SUPER STRONG is suitable on non-absorbent surfaces, imperfect prepared substrates, or humid walls. We suggest, in case of humid wall, to prepare the surface with ACM PRIMER SP.

### PACKAGES

Bucket 5 Kg  
Bucket 10 Kg  
Bucket 15 Kg

code 10004-C-SS  
code 10005-C-SS  
code 10006-C-SS

### STORAGE

TEXRECO CONTRACT SUPER STRONG is guaranteed for 24 months from the date of production.  
Preserve from frost (+ 5 °C + 40 °C).

### TECHNICAL DATA

base:	starch
physical appearance:	white cream
pH:	6,5
viscosity:	50,000 to 60,000 cps
V.O.C. content:	<0,55 g / l
solid content %:	about 35%
customs code:	3506 9190
application temperature:	+ 5 °C + 40 °C
waiting time:	0 - 10 minutes
open time:	20 - 30 minutes
definitive adhesion:	48 hours
non flammable	

### FINAL PROVISIONS

Keep out of the reach of children and pets. Discharge the waste in special containers for building materials.



A.C.M. Sas di Danese R. & C. | Via XXV Aprile, 62 | 20010 Bareggio /MI  
PHONE +39 02 903 611 48 | [laboratorio@acm-italy.com](mailto:laboratorio@acm-italy.com) | [www.acm-italy.com](http://www.acm-italy.com)